

## Translation of PCT/JP02/02974

## SPECIFICATION

## 5 Communication Apparatus and Communication Method

## Technical Field

The present invention relates to a communication apparatus incorporating a telephone function and a digital broadcast  
10 receiving function, and a communication method of transmitting/receiving telephone audio data and receiving a digital broadcast.

## Background Art

15 Rapid growth of mobile phones results greatly from the fact that they are equipped not only with the original telephone function but also with other functions such as the WEB browser function and the email function. Mobile phones are still now evolving with additional functions such as the Java application  
20 function and the video phone function.

Japan has already launched Digital Satellite Broadcasting services such as CS (Communication Satellite) and BS (Broadcasting Satellite), and scheduled to launch digitalized broadcasting services also for ground-based broadcasting in 2003.  
25 Terminals for receiving ground-based digitalized broadcasting

have been developed to include even a mobile terminal for local reception, and thus preparations have been carried out for the start of the services.

Future mobile phones are projected to include functions  
5 for receiving digitalized broadcasts as well as the WEB browser function and the email function. At present, however, there seems to exist no prior art in the field of problems that the present invention is directed to solving.

Now, Japanese Unexamined Patent Publication No. Hei  
10 6-165073 will now be cited as a related art reference.

Fig. 8 shows the block diagram of the reference. According to this invention, when a mute button is pressed by a remote control transmitter 9 or a keyboard 8 attached to the body, muting is activated, and at the same time a caption decoder ON/OFF control  
15 unit 10 turns on a caption decoder 3 to display multiplexed caption data via a display processing unit 5.

While muted and the caption decoder is on, on the other hand, when a demute button is pressed by the remote control transmitter 9 or the keyboard 8 attached to the body, demuting  
20 is activated and at the same time the caption decoder ON/OFF control unit 10 turns off the caption decoder 3 so that video is displayed alone via the display processing unit 5.

Japanese Unexamined Patent Publication No. Hei 6-165073 is directed to muting and displaying caption data, but not to  
25 implementing other functions.

With a projected future integration of a mobile phone and a digital broadcasting receiver, it may be assumed that a call is received or otherwise requested while a digital broadcast program is received.

5 Furthermore, the display of a future hybrid terminal of a mobile phone and a digital broadcast receiver can be anticipated small in size. This may pose a problem of conspicuousness with a constant caption display.

10 The present invention is directed to allowing calling on the phone "while" receiving a digital broadcast, and minimizing the period of caption display of a digital broadcast.

#### Disclosure of the Invention

15 A communication apparatus according to the present invention is characterized by including:

a multiplexed data receiving unit for receiving multiplexed data at least including audio data;

20 an extracting unit for extracting the audio data from the multiplexed data;

a telephone unit for transmitting/receiving telephone audio data;

25 an audio output unit for inputting one of extracted audio data that was extracted by the extracting unit and received telephone audio data that was received by the telephone unit,

and outputting one of the extracted audio data inputted and the received telephone audio data inputted;

a switching control unit for switching an input to the audio output unit between the extracted audio data and the  
5 received telephone audio data; and

an instructing unit for detecting a receive event generation, a send event generation, and an end event generation, and giving a prescribed instruction to the telephone unit, the extracting unit, and the switching control unit.

10 Then, the instructing unit, in the case of detecting one of the receive event generation and the send event generation while the multiplexed data is received by the multiplexed data receiving unit, transmits a telephone audio data transmission/reception start instruction to the telephone unit  
15 to start transmitting/receiving the telephone audio data, transmits an audio data extraction stop instruction to the extracting unit to stop extracting the audio data, and transmits a received telephone audio data switch instruction to the switching control unit to switch to the received telephone audio  
20 data, and in the case of detecting the end event generation while the multiplexed data is received by the multiplexed data receiving unit, transmits a telephone audio data transmission/reception stop instruction to the telephone unit to stop transmitting/receiving the telephone audio data,  
25 transmits an audio data extraction start instruction to the

extracting unit to start extracting the audio data, and transmits an extracted audio data switch instruction to the switching control unit to switch to the extracted audio data.

Then, the telephone unit, in the case of receiving the  
5 telephone audio data transmission/reception start instruction from the instructing unit, starts transmitting/receiving the telephone audio data, and in the case of receiving the telephone audio data transmission/reception stop instruction from the instructing unit, stops transmitting/receiving the telephone  
10 audio data.

Then, the extracting unit, in the case of receiving the audio data extraction stop instruction from the instructing unit, stops extracting the audio data, and in the case of receiving the audio data extraction start instruction, starts extracting  
15 the audio data.

Then, the switching control unit, in the case of receiving the received telephone audio data switch instruction from the instructing unit, switches the input to the audio output unit to the received telephone audio data, and in the case of receiving  
20 the extracted audio data switch instruction from the instructing unit, switches the input to the audio output unit to the extracted audio data.

The multiplexed data receiving unit is characterized by  
25 receiving multiplexed data including video data and text data.

Then, the extracting unit is characterized by extracting the video data from the multiplexed data, and also extracts the text data in a prescribed case.

Then, the communication apparatus is characterized by  
5 further including a display output unit for outputting extracted video data that was extracted by the extracting unit, and for outputting extracted text data in the case where the text data was extracted by the extracting unit.

Then, the instructing unit is characterized by  
10 transmitting a text data extraction start instruction to the extracting unit to start extracting the text data in the case of detecting one of the receive event generation and the send event generation while the multiplexed data is received by the multiplexed data receiving unit, and transmitting a text data  
15 extraction stop instruction to the extracting unit to stop extracting the text data in the case of detecting the end event generation while the multiplexed data is received by the multiplexed data receiving unit.

Then, the extracting unit is characterized by starting  
20 extracting the text data in the case of receiving the text data extraction start instruction from the instructing unit, and stopping extracting the text data in the case of receiving the text data extraction stop instruction from the instructing unit.

25 The audio output unit is characterized by being an

amplified audio output unit for amplifying volume of and then outputting one of the extracted audio data inputted and the received telephone audio data inputted and outputting.

Then, the communication apparatus is characterized by  
5 further including:

a ear audio output unit for outputting the received telephone audio data in a prescribed case; and

an amplified audio ear audio selecting unit for selecting one of the amplified audio output unit and the ear audio output  
10 unit, and making the one of the amplified audio output unit and the ear audio output unit output the received telephone audio data based on a selected result.

Then, the instructing unit is characterized by transmitting an amplified audio select instruction to the  
15 amplified audio ear audio selecting unit to select the amplified audio output unit in the case of detecting one of the receive event generation and the send event generation while the multiplexed data is received by the multiplexed data receiving unit.

20 Then, the amplified audio ear audio selecting unit is characterized by selecting the amplified audio output unit in the case of receiving the amplified audio select instruction from the instructing unit, and making the amplified audio output unit output the received telephone audio data.

The communication apparatus is characterized by further including:

a multiplexed data reception start time managing unit, for managing time for the multiplexed data receiving unit to start receiving the multiplexed data as multiplexed data reception start time, transmitting with an arrival of the multiplexed data reception start time a multiplexed data reception start instruction to the multiplexed data receiving unit to start receiving the multiplexed data, and transmitting a multiplexed data reception start notification to the instructing unit of a start of receiving the multiplexed data by the multiplexed data receiving unit.

Then, the multiplexed data receiving unit is characterized by starting receiving the multiplexed data in the case of receiving the multiplexed data reception start instruction from the multiplexed data reception start time managing unit.

Then, the instructing unit is characterized by judging whether the telephone audio data is being transmitted/received by the telephone unit upon receiving the multiplexed data reception start notification from the multiplexed data reception start time managing unit, and transmitting the audio data extraction stop instruction to the extracting unit in the case where the telephone audio data is being transmitted/received by the telephone unit, so that the instructing unit does not transmits the extracted audio data switch instruction to the



switching control unit.

The communication apparatus is characterized by further including:

5           a multiplexed data reception start time managing unit,  
for managing time for the multiplexed data receiving unit to  
start receiving the multiplexed data as multiplexed data  
reception start time, transmitting with an arrival of the  
multiplexed data reception start time a multiplexed data  
10 reception start instruction to the multiplexed data receiving  
unit to start receiving the multiplexed data, and transmitting  
a multiplexed data reception start notification to the  
instructing unit of a start of receiving the multiplexed data  
by the multiplexed data receiving unit.

15           Then, the multiplexed data receiving unit is characterized  
by starting receiving the multiplexed data in the case of  
receiving the multiplexed data reception start instruction from  
the multiplexed data reception start time managing unit.

          Then, the instructing unit is characterized by judging  
20 whether the telephone audio data is being transmitted/received  
by the telephone unit upon receiving the multiplexed data  
reception start notification from the multiplexed data reception  
start time managing unit, and transmitting the text data  
extraction start instruction to the extracting unit in the case  
25 where the telephone audio data is being transmitted/received

by the telephone unit.

The communication apparatus is characterized by further including:

- 5       a vibrator; and
- a vibrator control unit for controlling the vibrator.

Then, the instructing unit is characterized by judging whether the telephone audio data is being transmitted/received by the telephone unit in the case of receiving the multiplexed data reception start notification from the multiplexed data  
10       reception start time managing unit, and transmitting a vibrator start instruction to the vibrator control unit to start the vibrator in the case where the telephone audio data is being transmitted/received by the telephone unit.

15       Then, the vibrator control unit is characterized by starting the vibrator in the case of receiving the vibrator start instruction from the instructing unit.

The communication apparatus is characterized by being a  
20       mobile type communication apparatus.

A communication method according to the present invention is characterized by including:

- a multiplexed data receiving step for receiving
- 25       multiplexed data at least including audio data;

an extracting step for extracting the audio data from the multiplexed data;

a telephone audio data transmitting/receiving step for transmitting/receiving telephone audio data;

5        an audio output step for inputting one of extracted audio data that was extracted by the extracting step and received telephone audio data that was received by the telephone audio data transmitting/receiving step, and outputting one of the extracted audio data inputted and the received telephone audio  
10    data inputted;

a switching control step for switching an input to the audio output step between the extracted audio data and the received telephone audio data; and

an instructing step for detecting a receive event  
15    generation, a send event generation, and an end event generation, and giving a prescribed instruction to the telephone audio data transmitting/receiving step, the extracting step, and the switching control step.

Then, the instructing step, in the case of detecting one  
20    of the receive event generation and the send event generation while the multiplexed data is received by the multiplexed data receiving step, gives a telephone audio data transmission/reception start instruction to the telephone audio transmitting/receiving step to start transmitting/receiving  
25    the telephone audio data, gives an audio data extraction stop

instruction to the extracting step to stop extracting the audio data, and gives a received telephone audio data switch instruction to the switching control step to switch to the received telephone audio data, and in the case of detecting the  
5 end event generation while the multiplexed data is received by the multiplexed data receiving step, gives a telephone audio data transmission/reception stop instruction to the telephone audio transmitting/receiving step to stop transmitting/receiving the telephone audio data, gives an audio  
10 data extraction start instruction to the extracting step to start extracting the audio data, and gives an extracted audio data switch instruction to the switching control step to switch to the extracted audio data.

Then, the telephone audio transmitting/receiving step,  
15 in the case of receiving the telephone audio data transmission/reception start instruction from the instructing step, starts transmitting/receiving the telephone audio data, and in the case of receiving the telephone audio data transmission/reception stop instruction from the instructing  
20 step, stops transmitting/receiving the telephone audio data.

Then, the extracting step, in the case of receiving the audio data extraction stop instruction from the instructing step, stops extracting the audio data, and in the case of receiving the audio data extraction start instruction, starts extracting  
25 the audio data.

Then, the switching control step, in the case of receiving the received telephone audio data switch instruction from the instructing step, switches the input to the audio output step to the received telephone audio data, and in the case of receiving  
5 the extracted audio data switch instruction from the instructing step, switches the input to the audio output step to the extracted audio data.

The multiplexed data receiving step is characterized by  
10 receiving multiplexed data including video data and text data.

Then, the extracting step is characterized by extracting the video data from the multiplexed data, and also extracting the text data in a prescribed case.

Then, the communication method is characterized by further  
15 including:

a display output step for outputting extracted video data that was extracted by the extracting step, and in the case where the text data was extracted by the extracting step, outputting extracted text data that was extracted.

20 Then, the instructing step is characterized by giving a text data extraction start instruction to the extracting step to start extracting the text data in the case of detecting one of the receive event generation and the send event generation while the multiplexed data is received by the multiplexed data  
25 receiving step, and giving a text data extraction stop

instruction to the extracting step to stop extracting the text data in the case of detecting the end event generation while the multiplexed data is received by the multiplexed data receiving step.

5           Then, the extracting step is characterized by starting extracting the text data in the case of receiving the text data extraction start instruction from the instructing step, and stopping extracting the text data in the case of receiving the text data extraction stop instruction from the instructing step.

#### 10   Brief Description of the Drawings

Fig. 1 is a block diagram of a hybrid terminal of a mobile phone and a digital broadcast receiver according to a first embodiment.

15           Fig. 2 is a flowchart illustrating a control flow for receiving a phone call.

Fig. 3 is a diagram illustrating events and states that are managed by an event analysis processing unit.

20           Fig. 4 is a block diagram of a hybrid terminal of a mobile phone and a digital broadcast receiver according to a second embodiment.

Fig. 5 is a block diagram of a hybrid terminal of a mobile phone and a digital broadcast receiver according to a third embodiment.

25           Fig. 6 is a flowchart illustrating a control flow for starting the reception of a digital broadcast.

Fig. 7 is a block diagram of a hybrid terminal of a mobile phone and a digital broadcast receiver according to a fourth embodiment.

Fig. 8 shows conventional art.

5

#### Best Mode for Carrying out the Invention Embodiment 1.

Fig. 1 shows a hybrid terminal for mobile phone and digital broadcast reception according to a first embodiment of the present invention. With referring to the figure, a reference numeral 101 denotes a digital broadcast tuner unit, a reference numeral 102 denotes a digital broadcast demodulating unit, a reference numeral 103 denotes a multiplexed transmission separating unit, a reference numeral 104 denotes a program information processing unit, a reference numeral 105 denotes a caption/data broadcast processing unit, a reference numeral 106 denotes a digital broadcast video processing unit, a reference numeral 107 denotes a digital broadcast audio processing unit, a reference numeral 108 denotes a display superimposing unit, a reference numeral 109 denotes an audio path switching control unit, a reference numeral 110 denotes a display output unit, a reference numeral 111 denotes an audio output unit, a reference numeral 112 denotes an event analysis processing unit, a reference numeral 113 denotes a telephone RF unit, a reference numeral 114 denotes a telephone audio

10

15

20

25

processing unit, a reference numeral 115 denotes an audio input unit, a reference numeral 116 denotes a call start/end button, a reference numeral 117 denotes a CPU, and a reference numeral 118 denotes a memory.

5           The digital broadcast tuner unit 101 receives a digital broadcast wave including video data, audio data, and caption data (text data) multiplexed. The digital broadcast tuner unit 101 is an example of a multiplexed data receiving unit, and the digital broadcast wave that the digital broadcast tuner unit  
10 101 receives is an example of multiplexed data.

          The digital broadcast demodulating unit 102 demodulates the digital broadcast wave received at the digital broadcast tuner unit 101.

          The multiplexed transmission separating unit 103  
15 separates a relevant stream or section data from the multiplexed data (extracting video data, audio data, etc.). This is well known art in digital broadcast processing, and therefore will not be elaborated here. The multiplexed transmission  
separating unit 103 stops separating digital broadcast audio  
20 data and starts separating caption data in a prescribed case. It is to be noted that the multiplexed transmission separating unit 103 is an example of an extracting unit. Also, video data separated by the multiplexed transmission separating unit 103 corresponds to extracted video data, audio data separated by  
25 the multiplexed transmission separating unit 103 corresponds



to extracted audio data, and caption data separated by the multiplexed transmission separating unit 103 corresponds to extracted text data.

The program information processing unit 104 can judge the  
5 presence or absence of monomedia, such as video data, audio data, and caption data (text data) that are multiplexed in a broadcast program, and a data broadcast, and know the separation information thereof based on incoming program information carried by the digital broadcast wave. This is well known art  
10 in digital broadcast processing, and therefore will not be elaborated here. Also, the program information processing unit 104 gives instructions with reference to program information to the multiplexed transmission separating unit 103 to stop separating the audio data of a digital broadcast, and to start  
15 separating caption data if the digital broadcast includes the caption data. In the absence of caption data, the program information processing unit 104 gives instructions only to stop separating the audio data of a digital broadcast and perform muting.

20 It is to be noted that the program information processing unit 104, as well as the event analysis processing unit 112 which is described later, corresponds to an example of an instructing unit.

The caption/data broadcast processing unit 105 performs  
25 data processing required for displaying caption data and various

types of other data (such as decoding caption data).

The digital broadcast video processing unit 106 performs data processing required for displaying video data (such as decoding video data).

5       The digital broadcast audio processing unit 107 performs data processing required for outputting audio data (such as decoding audio data). Also, it mutes audio data in a prescribed case.

10       The display superimposing unit 108 has the function of superimposing video data onto different video data, or superimposing caption data onto video data. Also, it displays superimposed video data or caption data on the display output unit 110. This is well known art in digital broadcast processing, and therefore will not be elaborated here.

15       The display output unit 110 displays data superimposed by the display superimposing unit 108.

20       The audio path switching control unit 109 switches the audio path (input to the audio output unit 111) to the telephone side or the digital broadcast audio side, and makes audio output through the audio output unit 111. It is to be noted that the audio path switching control unit 109 is an example of a switching control unit.

25       The audio output unit 111 outputs telephone audio data from the telephone audio processing unit 114 when the audio path is on the telephone side, and outputs audio data from the digital

broadcast audio processing unit 107 when the audio path is on the digital broadcast audio side.

The event analysis processing unit 112 gives instructions to the program information processing unit 104 to mute a digital broadcast and display caption data, upon receiving or transmitting a call while the user is watching and listening to the digital broadcast. Also, the event analysis processing unit 112 at the same time gives instructions to the audio path switching control unit 109 to switch the audio path to the output side of the telephone audio processing unit. Also, when the user ends a call while at the same time receiving a digital broadcast, the event analysis processing unit 112 gives instructions to the program information processing unit 104 to restore the audio data of the digital broadcast and delete the caption data. Still also, the event analysis processing unit 112 gives instructions to the audio path switching control unit 109 to switch the audio path to the output side of the digital broadcast audio processing unit 107.

It is to be noted that a combination of the event analysis processing unit 112 and the program information processing unit 104 corresponds to an instructing unit.

The telephone RF unit 113, the telephone audio processing unit 114, the audio input unit 115 and the call start/end button 116 are components for implementing the telephone function and correspond to a telephone unit if combined.

Also, the hybrid terminal according to this embodiment is an example of a communication apparatus.

An operation will now be discussed.

Firstly, a description will be given of the case of  
5 receiving a call while the user is watching and listening to a digital broadcast program.

This case includes the situation that a digital broadcast wave is being received by the digital broadcast tuner unit 101, the separation processing of video data and audio data is being  
10 performed in the multiplexed transmission separating unit 103, video data is being outputted from the display output unit 110, and audio data is being outputted from the audio output unit 111. Meanwhile, the audio path is set on the side of the digital broadcast audio by the audio path switching control unit 109.

15 Upon receiving a call while the user is watching and listening to a digital broadcast program, the telephone RF unit 113 sends a receive event to the event analysis processing unit 112.

The event analysis processing unit 112 detects the receive  
20 event and gives instructions to the program information processing unit 104 to mute the digital broadcast audio and display the caption data. At the same time, the event analysis processing unit 112 transmits an instruction message (received telephone audio data switch instruction) to the audio path  
25 switching control unit 109, instructing to switch the audio path

to the output side of the telephone audio processing unit 114.

The program information processing unit 104 transmits an instruction message to the multiplexed transmission separating unit 103 with reference to the program information. More specifically, the program information processing unit 104 transmits an instruction message to stop separating the audio data of the digital broadcast (audio data extraction stop instruction). In the case of having caption data, the program information processing unit 104 transmits an instruction message to start separating the caption data (text data extraction start instruction). Without having caption data, it instructs to stop separating the audio data of the digital broadcast only.

The multiplexed transmission separating unit 103 stops separating the audio data of the digital broadcast and starts separating the caption data. The digital broadcast audio processing unit 107 performs muting and the caption/data broadcast processing unit 105 decodes the caption data.

The display superimposing unit 108 superimposes the caption data onto the video data and displays it on the display output unit 110.

In the meantime, the audio path switching control unit 109 switches the audio path to the telephone side.

When the user presses the call start/end button 116, the event analysis processing unit 112 receives a call start event and transmits an instruction message (telephone audio data

transmission/reception start instruction) to the telephone RF unit 113, indicating to start transmitting/receiving telephone audio data, so as to make a call start.

The same process is applicable to the case where the user  
5 makes a phone call while watching and listening a digital broadcast program.

More particularly, when the user presses the call start/end button 116, the event analysis processing unit 112 detects a send event, and instructs the program information processing  
10 unit 104 to mute the digital broadcast audio and display the caption data. At the same time, the event analysis processing unit 112 transmits an instruction message (received telephone audio data switch instruction) to the audio path switching control unit 109 to switch the audio path to the output side  
15 of the telephone audio processing unit 114.

Then, the program information processing unit 104, with reference to the program information, transmits to the multiplexed transmission separating unit 103 an instruction message (audio data extraction stop instruction) to stop  
20 separating the audio data of the digital broadcast, and an instruction message (text data extraction start instruction) to start separating the caption data with the presence of the caption data. The multiplexed transmission separating unit 103 stops separating the audio data of the digital broadcast and  
25 starts separating the caption data. The digital broadcast audio

processing unit 107 starts muting and the caption/data broadcast processing unit 105 starts decoding the caption data.

The display superimposing unit 108 superimposes the caption data onto the video data, and displays it on the display  
5 output unit 110.

In the meantime, the audio path switching control unit 109 switches the audio path to the telephone side.

Also, in the meantime, the event analysis processing unit 112 transmits an instruction message (telephone audio data  
10 transmission/reception start instruction) to the telephone RF unit 113 to start transmitting/receiving telephone audio data so as to make a call start.

An operation will be discussed of the case where the user ends a call.

15 It is to be noted that this case includes the situation that a digital broadcast wave is being received by the digital broadcast tuner unit 101, and the separation of video data and caption data is in process in the multiplexed transmission separating unit 103, whereas the separation of audio data is  
20 stopped, and the video data and the caption data are being outputted from the display output unit 110. In the meantime, telephone audio data is being transmitted/received through the telephone RF unit 113, the telephone audio processing unit 114, and the audio input unit 115, and telephone audio data is being  
25 outputted from the audio output unit 111. Also, in the meantime,

the audio path is set on the telephone side by the audio path switching control unit 109.

When the user presses the call start/end button 116, the event analysis processing unit 112 detects an end event, and  
5 transmits an instruction message (telephone audio data transmission/reception stop instruction) to the telephone RF unit 113 so as to make the call end.

If a dialoguer (the other party) ends the call first, then the telephone RF unit 113 gives the end event to the event analysis  
10 processing unit 112.

Also, the event analysis processing unit 112 at the same time instructs the program information processing unit 104 to start separating the audio data of the digital broadcast (digital broadcast audio return) and stop separating the caption data  
15 (caption deletion). Still also, the event analysis processing unit 112 transmits an instruction message (extracted audio data switch instruction) to the audio path switching control unit 109 to switch the audio path to the output side of the digital broadcast audio processing unit 107.

20 The program information processing unit 104 transmits an instruction message (audio data extraction start instruction and text data extraction stop instruction) to the multiplexed transmission separating unit 103, instructing to start separating the audio data of the digital broadcast and stop  
25 separating the caption data.



The multiplexed transmission separating unit 103 starts separating the audio data of the digital broadcast and stop separating the caption data, and the digital broadcast audio processing unit 107 starts decoding the audio and the  
5 caption/data broadcast processing unit 105 stops decoding the caption data.

As a result, the display superimposing unit 108 displays video data outputted from the digital broadcast video processing unit 106 alone on the display output unit 110.

10 The audio path switching control unit 109, upon receiving the instruction message from the event analysis processing unit 112, switches the audio path to the digital broadcast audio side and makes the audio data of the digital broadcast output from the audio output unit 111.

15 Fig. 2 shows a flow of an internal operation of the hybrid terminal upon receiving/transmitting a call. Fig. 3 shows an example of events/states that the event analysis processing unit handles. Fig. 3(a) includes the states to be managed by the event analysis processing unit. Fig. 3(b) includes events to  
20 be managed by the event analysis processing unit.

The thus configured hybrid terminal of a mobile phone and a digital broadcast receiver allows providing the user with calling and receiving a digital broadcast  
upon receiving/transmitting a call while at the same time  
25 receiving the digital broadcast. In addition, this hybrid

terminal, being thus designed to displaying caption data only while the phone is used, allows reducing the period of displaying caption data on a small screen.

5 Embodiment 2.

Fig. 4 shows a hybrid terminal of a mobile phone equipped with a hands free function and a digital broadcast receiver according to a second embodiment of the present invention. With referring to the figure, a reference numeral 101 denotes a digital  
10 broadcast tuner unit, a reference numeral 102 denotes a digital broadcast demodulating unit, a reference numeral 103 denotes a multiplexed transmission separating unit, a reference numeral 104 denotes a program information processing unit, a reference numeral 105 denotes a caption/data broadcast processing unit,  
15 a reference numeral 106 denotes a digital broadcast video processing unit, a reference numeral 107 denotes a digital broadcast audio processing unit, a reference numeral 108 denotes a display superimposing unit, a reference numeral 109 denotes an audio path switching control unit, a reference numeral 110  
20 denotes a display output unit, a reference numeral 111 denotes an audio output unit, a reference numeral 112 denotes an event analysis processing unit, a reference numeral 113 denotes a telephone RF unit, a reference numeral 114 denotes a telephone audio processing unit, a reference numeral 115 denotes an audio  
25 input unit, a reference numeral 116 denotes a call start/end

button, a reference numeral 117 denotes a CPU, a reference numeral 118 denotes a memory, a reference numeral 201 denotes a hands free control unit, a reference numeral 202 denotes an amplified audio output unit, and a reference numeral 203 denotes a ear  
5 audio output unit.

The amplified audio output unit 202 is to output the telephone audio data of the mobile phone in the hands free mode and the audio data of a digital broadcast. The ear audio output unit 203 is to output the telephone audio data of the mobile  
10 phone in the normal mode.

The hands free control unit 201 provides on/off control of the hands free function. The hands free function is well known art of mobile phone, and therefore will not be elaborated here. It is to be noted that the hands free control unit 201  
15 is an example of an amplified audio ear audio selecting unit.

Similarly to the first embodiment, the audio path is switched to the telephone side by the event analysis processing unit 112 upon receiving/transmitting a mobile phone call while at the same time receiving a digital broadcast. In this case,  
20 however, the event analysis processing unit 112 makes a request to the hands free control unit 201 for turning on the hands free mode (transmitting an amplified audio selection instruction), and the hands free control unit 201 turns on the hands free mode (selecting an amplified audio output unit.) It is to be noted  
25 that the other parts of processing is the same as those discussed

in the first embodiment.

The thus configured hybrid terminal of a mobile phone and a digital broadcast receiver, being designed to automatically select the hands free mode upon receiving a call while at the same time receiving a digital broadcast, allows a pleasant call on the mobile phone while at the same time receiving a digital broadcast.

### Embodiment 3.

Fig. 5 shows a hybrid terminal of a mobile phone capable of presetting reception of programs and a digital broadcast receiver according to a third embodiment of the present invention. With referring to the figure, a reference numeral 101 denotes a digital broadcast tuner unit, a reference numeral 102 denotes a digital broadcast demodulating unit, a reference numeral 103 denotes a multiplexed transmission separating unit, a reference numeral 104 denotes a program information processing unit, a reference numeral 105 denotes a caption/data broadcast processing unit, a reference numeral 106 denotes a digital broadcast video processing unit, a reference numeral 107 denotes a digital broadcast audio processing unit, a reference numeral 108 denotes a display superimposing unit, a reference numeral 109 denotes an audio path switching control unit, a reference numeral 110 denotes a display output unit, a reference numeral 111 denotes an audio output unit, a reference numeral 112 denotes

an event analysis processing unit, a reference numeral 113 denotes a telephone RF unit, a reference numeral 114 denotes a telephone audio processing unit, a reference numeral 115 denotes an audio input unit, a reference numeral 116 denotes  
5 a call start/end button, a reference numeral 117 denotes a CPU, a reference numeral 118 denotes a memory, and a reference numeral 301 denotes a reception preset processing unit.

The reception preset processing unit 301 analyzes the schedule of a program based on program information that is  
10 transmitted via a digital broadcast wave, and presets the program for reception. This is well known art in digital broadcast processing, and therefore will not be elaborated here. It is to be noted that the reception preset processing unit 301 is a multiplexed data reception start time managing unit.

15 According to the third embodiment of the present invention, when a preset program for reception starts via a preset function of the reception preset processing unit 301, the reception preset processing unit 301 instructs the digital broadcast tuner unit 101 to start a reception (transmitting a multiplexed data  
20 reception start instruction), and at the same time gives a reception start event to the event analysis processing unit 112 (transmitting a multiplexed data reception start notification). The event analysis processing unit 112 judges whether or not the user is on the telephone, and in other words judges whether  
25 or not telephone audio data is being transmitted/received.

When the user is on the telephone (telephone audio data is being transmitted/received), the event analysis processing unit 112 instructs the program information processing unit 104 to mute the digital broadcast audio and display the caption data.

5 Also, the event analysis processing unit 112, without instructing the audio path switching control unit 109 to switch the audio path, keeps the audio path on the telephone side. It is to be noted that the other parts of processing is the same as those discussed in the first embodiment.

10 Fig. 6 shows a control flow upon starting to receive a digital broadcast.

It is desirable that the hands free mode is selected for calling as discussed in the second embodiment.

The thus configured hybrid terminal of a mobile phone and  
15 a digital broadcast receiver allows using the mobile phone while at the same time receiving a digital broadcast, even if a digital broadcast program preset for reception started while using the phone.

#### 20 Embodiment 4.

Fig. 7 shows a hybrid terminal of a mobile phone capable of presetting reception of programs and a digital broadcast receiver according to a fourth embodiment of the present invention. With referring to the figure, a reference numeral  
25 101 denotes a digital broadcast tuner unit, a reference numeral

102 denotes a digital broadcast demodulating unit, a reference numeral 103 denotes a multiplexed transmission separating unit, a reference numeral 104 denotes a program information processing unit, a reference numeral 105 denotes a caption/data broadcast processing unit, a reference numeral 106 denotes a digital broadcast video processing unit, a reference numeral 107 denotes a digital broadcast audio processing unit, a reference numeral 108 denotes a display superimposing unit, a reference numeral 109 denotes an audio path switching control unit, a reference numeral 110 denotes a display output unit, a reference numeral 111 denotes an audio output unit, a reference numeral 112 denotes an event analysis processing unit, a reference numeral 113 denotes a telephone RF unit, a reference numeral 114 denotes a telephone audio processing unit, a reference numeral 115 denotes an audio input unit, a reference numeral 116 denotes a call start/end button, a reference numeral 117 denotes a CPU, a reference numeral 118 denotes a memory, a reference numeral 301 denotes a reception preset processing unit, a reference numeral 401 denotes a vibrator control unit, and a reference numeral 402 denotes a vibrator.

The vibrator control unit 401 and the vibrator 402 are used for informing of the reception of a mobile phone call as well. This is well known art, and therefore will not be elaborated here.

According to the fourth embodiment of the present invention,

when a program preset for reception starts via the preset function of the reception preset processing unit 301, the event analysis processing unit 112 receives a reception start event, and judges whether or not the user is on the telephone.

5           When the user is on the telephone, an instruction message (vibrator start instruction) is transmitted to the vibrator control unit 401, instructing to turn on the vibrator, and the vibrator control unit 401 makes the vibrator 402 start.

          The same operations as those of the first embodiment of  
10 the present invention follow subsequently.

          The thus configured hybrid terminal of a mobile phone and a digital broadcast receiver allows the user on the phone to know the start of a program preset for reception easily by applying the vibrator, which is designed originally for notifying of the  
15 reception of a mobile phone call, to the start notification of a program preset for reception as well.

          It is desirable that the hands free mode is selected for calling as discussed in the second embodiment.

20           With reference to the first to fourth embodiments, descriptions were given of the hybrid terminal of a mobile phone and a digital broadcast receiver as an example. Alternatively, however, the mechanisms discussed in the first to fourth embodiments are also applicable to a hybrid terminal of a wired  
25 fixed telephone and a digital broadcast receiver.



Further with reference to the first to fourth embodiments, descriptions were given of the hybrid terminal receiving digital broadcasts as an example. Alternatively, however, the mechanism discussed in the first to fourth embodiments is also  
5 applicable to a hybrid terminal receiving analog broadcasts.

Still further with reference to the first to fourth embodiments, descriptions were given of the communication apparatus according to this invention as an example. Alternatively, however, a communication method may also be  
10 implemented according to this invention based on the processing procedures discussed in the first to fourth embodiments.

Now, the characteristics of the hybrid terminal discussed in the first to fourth embodiment will be reiterated below.

The hybrid terminal discussed in the first to fourth  
15 embodiments is characterized by including the tuner unit for receiving a digital broadcast, the digital broadcast demodulating unit for demodulating the digital broadcast, the multiplexed transmission separating unit for separating multiplexed transmission data, the program information  
20 processing unit for analyzing the program information, instructing the digital broadcast tuner unit to select a station and instructing the multiplexed transmission separating unit to carry out the separation, the caption/data broadcast  
processing unit for decoding a caption data broadcast separated  
25 by the multiplexed transmission separating unit, the digital

broadcast video processing unit for decoding a video broadcast also separated by the multiplexed transmission separating unit, the digital broadcast audio processing unit for decoding digital broadcast audio separated alike by the multiplexed transmission  
5 separating unit, the display superimposing unit for superimposing the caption/data broadcast onto the video broadcast, the telephone RF unit for carrying out telephone wireless processing, the telephone audio processing unit for processing telephone audio, the event analysis processing unit  
10 for analyzing/processing the receive/send event of a call, the audio path switching control unit for switching between the digital broadcast audio output and the telephone audio output, and the audio output unit.

Then, the hybrid terminal is characterized by switching  
15 the audio path to the telephone side, displaying a caption, and allowing calling, in the case of receiving a call while at the same time receiving a digital broadcast, and in the case where the call is finished, switching the audio path to the digital broadcast audio side, deleting the caption, and displaying the  
20 digital broadcast video alone.

The hybrid terminal discussed in the first embodiment is characterized in that, upon receiving a call while at the same time receiving a digital broadcast, the event analysis processing unit makes a request to the program information processing unit  
25 for displaying the caption separated and stopping separating

the digital broadcast audio/muting, and the event analysis processing unit also makes a request to the audio path switching control unit for switching the audio path, so that the caption display and the audio path are switched.

5       The hybrid terminal discussed in the first embodiment is characterized in that, upon transmitting a call while at the same time receiving a digital broadcast, the event analysis processing unit makes a request to the program broadcast processing unit for displaying the caption, and the event  
10 analysis processing unit also makes a request to the audio path switching control unit for switching the audio path, so that the caption display and the audio path are switched.

      The hybrid terminal discussed in the second embodiment is characterized by adding the hands free control unit, muting  
15 and displaying the caption upon receiving a call while at the same time receiving a digital broadcast, and switching at the same time to the hands free mode.

      The hybrid terminal discussed in the third embodiment is characterized by adding the reception preset processing unit,  
20 and also characterized in that the program information processing unit outputs the caption instead of the audio when a program preset for reception starts while the phone is used at the same time.

      The hybrid terminal discussed in the fourth embodiment  
25 is characterized by adding the vibrator control unit and the

vibrator, and also characterized in that, when a program preset for reception starts while the user is on the telephone at the same time, the start of the program is notified to the user via the vibrator, and the program information processing unit outputs  
5 the caption instead of the audio.

### Industrial Applicability

Thus, according to the present invention, in the case where the receive event or the send event is generated while the  
10 multiplexed data is received, the audio output is switched so that the received telephone audio data is outputted, and in the case where the end event is generated while the multiplexed data is received, the audio output is switched so that the extracted audio data is outputted. Hence, both receiving/outputting the  
15 multiplexed data and calling may be implemented.

Furthermore, according to the present invention, in the case where the receive event or the send event is generated while the multiplexed data is received, the extracted text data is started to be displayed, and in the case where the end event  
20 is generated while the multiplexed data is received, the extracted text data is stopped being displayed. Hence, the period of displaying text data may be minimized.

Still further according to the present invention, in the case where the receive event or the send event is generated while  
25 the multiplexed data is received, the amplified audio is

outputted. Hence, both receiving/outputting the multiplexed data and calling may be implemented with hands free.

Still further according to the present invention, when telephone audio is being transmitted/received at the multiplexed data reception start time, switching to the extracted audio data is not performed. Hence, both receiving/outputting the multiplexed data and calling may be implemented even in the event that the reception is started of the multiplexed data while the phone is used at the same time.

10 Still further according to the present invention, when telephone audio data is being transmitted/received at the multiplexed data reception start time, the vibrator is started. Hence, the start of receiving the multiplexed data may be notified via the vibrator even in the event that the reception is started  
15 of the multiplexed data while the phone is used at the same time.